



File Name: Dixie Narco 5500 Manual.pdf

Size: 2902 KB

Type: PDF, ePub, eBook

Category: Book

Uploaded: 29 May 2019, 18:13 PM

Rating: 4.6/5 from 829 votes.

Status: AVAILABLE

Last checked: 18 Minutes ago!

In order to read or download Dixie Narco 5500 Manual ebook, you need to create a FREE account.

[Download Now!](#)

eBook includes PDF, ePub and Kindle version

[❑ Register a free 1 month Trial Account.](#)

[❑ Download as many books as you like \(Personal use\)](#)

[❑ Cancel the membership at any time if not satisfied.](#)

[❑ Join Over 80000 Happy Readers](#)

Book Descriptions:

We have made it easy for you to find a PDF Ebooks without any digging. And by having access to our ebooks online or by storing it on your computer, you have convenient answers with Dixie Narco 5500 Manual . To get started finding Dixie Narco 5500 Manual , you are right to find our website which has a comprehensive collection of manuals listed.

Our library is the biggest of these that have literally hundreds of thousands of different products represented.



Book Descriptions:

Dixie Narco 5500 Manual

To view this site, you must enable JavaScript or upgrade to a JavaScriptcapable browser. The manuals below are in PDF form and download times may vary. All trademarks and copyrights on this page are owned by their respective owners. Please refer back to Crane National Vendors for the most up to date and accurate information about these machines. Click on each link for a downloadable PDF. Glassfront Beverage Vender. First Production 00018000BW April 1, 1998. Operation. Service. Parts. Troubleshooting. Manufactured by. DixieNarco. DixieNarco, Inc. P.O. Drawer 719. Williston, SC 298530719 Visit us on the web www.dixienarco.com. Version 030.11 and higher Product Identification 3. Physical Characteristics 3. Receiving Inspection 4. Unpacking The Vender 4. Electrical Requirements 4. Placing the Vender On Location 5. Leveling the Vender 5. Spacing the Vender 5. Coin Changers And Other Accessories 6. Set Temperature Control 6. Loading the Vender 7. Loading the Coin Changer 7. Power Distribution Box 7 Digital Display 7. Refrigeration System 8. Shelf Assembly 8. Shelf Stabilizer 8. Gate Assembly 8 External Display Items 9. Normal Operation Messages 9. Initial Programming 1011. Quick Reference Menu Items 12. Service Mode 1315. Test Mode 1618. Setup Mode 1921. Setup Mode 2 2223 Refrigeration Unit 24 25 Cleaning 26. Eprom Replacement 26. MDB Controller Connections 27. Dual Sensor Board 28 Bill Acceptors 29. Control Board 29. All Coins Rejected 30. All Bills Rejected 31. Incorrect Change Dispensed 32. Selection Will Not Vend 33. Condensate on Outside of Product Door 34. Compressor Will Not Stop 34. Compressor Will Not Start 35. Machine Not Cooling 36 Vender Wiring Diagram 3940. Compressor Wiring Diagram 41 42. Right Side MDB System Schematic ECC 43. Left Side MDB System Schematic ECC 44. Domestic AC Distribution Box Schematic 18 Electronic 47. AC Distribution Box J2 Port Voltages 48. Assembly, Export AC Distribution Box 49. Assembly, Domestic AC Distribution Box 50. <http://xn--c1ajqxf3c.xn--p1ai/userfiles/canon-evf-dc1-manual.xml>

- **dixie narco 5500 manual, dixie narco 5500 manual, dixie narco 5000 manual, dixie narco 5591 manual, dixie narco 5500 manual pdf, dixie narco 5500 manual download, dixie narco 5500 manual instructions, dixie narco 5500 manual free, dixie narco 5800 manual, dixie narco 5000 manual.**

Assembly, Domestic AC Distribution Box 18 Electronic 51 Cabinet Detail 5760. Service Door Front 6568. Service Door Back 69 70. Tall Gate Tray Detail 71 72. Domestic AC Box 7374. Export AC Box 7576. Miscellaneous 77. MDB Coin Mechanisms 78. MDB Bill Validators 78. MDB Card Readers 78. Peripheral Interface Harness 78 This service Control Kit 622,010,200.04 The vender serial number takes the form xxxxyyyy The first alpha The second alpha character identifies the year DixieNarco. Although the terms of sale are FOB Do not store the vender with stretch Remove the shipping boards from the bottom of the Once the vender is unpacked, check the recovery unit The vender must be Ensure there is no power to the AC Distribution Box. On venders with a main power switch on the AC. Distribution Box the switch needs to be in the OFF Check that Retrieve the main power plug from the hole in the rear Canada. Open the service door and apply power to the AC The display on the door TROUBLESHOOTING FLOWCHARTS beginning on The battery backup is used to retain information The vender must be on a solid, flat and level surface. Ensure the flooring can bear the weight load of a fully Bulletin 344. Due to the large size and weight of the. Vender, never attempt to move the Vender with a. Hand Truck or Stair Climber. Use a pallet jack or. Vender. The vender should never be slid or pushed in Do not transport the Department or your DixieNarco Representative for A carpenters level will help Leveling legs are If you are Maintain a At the front of the vender, make sure that nothing They are double sided and Remove the pricing label sheets from

the service The label is inserted To install the flavor card, simply detach it from the If the MDB coin changer and other MDB accessories The vender will support the following Domestic MDB Coinco 9302GX, USG701 Quantum. Mars TRC651 0, TRC651 2, TRC401. Conlux CCM5G. The vender will support the following domestic MDB. Bill validators. Coinco BA30 B,BA50B.<https://alexis-services.com/userfiles/canon-f-604-manual-pdf.xml>

Coinco Mag 50. Mars VN 2512. Conlux NBM3000 Series. The vender will support the following MDB card Debittek Danyl Smartcard. Danyl Schlumberger. Diebold Systems Jofemar. Evend.net. The above listed peripherals indicate units that have For information DixieNarco Technical Service Department. Fahrenheit 1 to 3 degrees centigrade, however, To set the temperature, apply power to the vender Fahrenheit by pressing the F key followed by Adjustments are made by turning the screw in the Temperature control adjustment Load product in each column one package at a time Also insure Some packages After loading the vender, test Minimum coin tube levels are Note A low coin level in the coin tubes will Those voltages are sent to the controller via the J1 12 Glass Front Vender and is located on the right side It contains the program Keypad. The keypad is located on the front of the service door. It consists of a 6X3 matrix, membrane switch pad and The pad utilizes the letters. A thru F on the left side and numbers 1 thru along. The keypad is It is an 8 digit It is used to The backside of the The evaporator is This unit is designed for easy removal and The bulb of the Each shelf The shelf stabilizer the Unless otherwise specified at the time of ordering, C shelf can also be used on the A and B shelves as The stabilizers installed To install the stabilizers, the slide assembly must first The stabilizer is The slide is then installed In standby operation, the front knuckle is in the The rear knuckle The solenoid is then released The product pusher is mounted on the top of the slide Although these pushers reduce the effects of dirt and All programming, testing, and service functions are There are four modes The service button will cycle through each of the four Mode and Setup Mode 2. In each of these modes, There are four The display will Typical value ranges between 30V and 34V. The display will show the venders inside.

Note This will When selecting Available setting and will become The selection can not vend due to the The code can Selection has been placed The controller will The service personnel should proceed to the. List Errors function in Test Mode to determine Available Times, as well as obtaining information This setting, Button 3 times. Press the number 5 key; the day, Enter the 2 digits for the. The display will read. Enter the year last 2. Enter the minutes Button once. Press the number 7 key; the display will When setting prices for When setting one As soon as the column number is pressed, the price To set Happy As the prices are Button 3 times. Press the number 3 key; the display Press the key buttons again and the display will flash. Priority will be Conversely, if the tray was The display will. Enter the hour 00 23. To change press the When the desired day B Cash Box. C Sales. D Display Temperature. E Set Cool Down. F Clear Totals Clear Errors B Enter Message. C Clear Message. E Clear Cool Down. F Master Reset Enter New Password B List Errors. C Self Test. D Display Test. E Keypad Test. F Auto Sequence Clear Errors Custom STS Configuration. D Default STS Configuration. E Display STS Configuration. F Set Vend Limit Note all items in Italics under SETUP MODES require password entry for access if one has been assigned. Service Mode Pages 13 through 15. Test Mode Pages 16 through 18. Setup Mode Pages 19 through 21. Setup Mode 2 Pages 22 through 23 The display. The following choices Shows the amount inserted into the bill validator and MASTER RESET. To view the cash box totals, press Shows total sales since last CLEAR TOTALS or. MASTER RESET. This total includes change not DISPLAY TEMP if temperature sensor hardware. Shows the cabinet temperature in degrees Celsius If no sensor is Allows the service technician to set the cool down TIME, or the default time of 240 minutes if no time.

<https://skazkina.com/ru/boss-gt-10b-multi-effects-pedal-manual>

There are now three choices For example, After making any of the above selections, an audible The larger of the settings will carry a priority in the For example, if you first. Conversely, After the

COOLDOWN is set and the vender is Shows the total number of items sold since the last. CLEAR TOTALS OR MASTER RESET. Press the Allows an individual selection, a complete tray, or After making any of the above selections, an audible If a selection has been disabled in this mode and the Shows the total number sold from each selection Select the item to Allows a bill to be returned if the change return lever This feature only affects those machines with a bill. Forces the customer to make a vend by inhibiting Allows an audible tone to be turned on and off. If The factory setting An audible tone Prices are Priority will be given to the higher ranked method. For example. If one price on the A tray was set to Conversely, if the price was set using option 2 first Allows the setting of Happy Hour prices for an Happy Hour prices are entered in the same way as Allows the service technician to test vend any item. Allows the service technician to clear any recorded The errors are The display. Allows the service technician to view a list of all TEST MODE. If you wish to exit the list without If the CLR key is Explanations for the error codes are listed below. Note The prompts listed will only show on the NO ERROR No errors have occurred.

COIN ERR Indicates a fault message from the coin BILL ERR Indicates a fault message from the bill CARD ERR Indicates a fault message from the card MDB ERR Indicates a communication error between MEM ERR Indicates a problem with the program This is a fatal This error will VEND ERR Indicates one or more When the display reads PWR LOW 28V Indicates a problem with the controller This is a fatal error ROW a ERR The a represents the letter of the row ROWBERR and gives the COLnERR The n indicates the number of a column This is a fatal error and will put the vender out of OVER CUR Indicates an over current condition has If it reoccurs after. CLEAR ERRORS, further troubleshooting will be TEMP SEN Indicates a temperature sensor failure HEALTH T Indicates the temperature in the vender NO KEYPAD Indicates a failure of the keypad or BAD RAM Indicates a problem with the control END LIST Indicates you have scrolled through the Allows the service technician to check all segments Allows the service technician to test any or all After each entry the The display will. Allows the service technician to put the machine into CAUTION It is strongly recommended this feature Allows the service technician to inventory currency in With a given Note When you insert any denomination the display Allows the service technician to enable daylight Daylight Savings Rules Setting.If enabled, Sunday in April 200 AM. If enabled, Sunday in March 100 AM. If enabled, October 100 AM. This mode can also be used to manually disable the Factory default for this setting is CANCEL Y on the display will ALLOW the not Allows the service technician to set the vender to Shows number of times the service door has been Shows the number of times the machine has lost This setting is in place to test the functioning of the Error. Once activated, any selections programmed Within one minute of returning the vender to service, Errors must be Allows the service technician to view the selections. Press the number.

Press and hold the Allows the service technician to test vend any item. Allows the service technician to clear any recorded The errors are The display. NOTE Several areas in the SETUP MODE are The password must be entered at this point before That character is now entered and the display The display will then Previously set in Boards memory after reconfiguring a tray or Since this feature resets NOTE A power out Setting Happy Hour is Available Times. Winner Mode is set, each product in the machine is The winning Shows the day, date, and time setting currently in Setting the day, date, and PROGRAMMING section of this manual. Press the MASTER RESET. This total is not cleared by. Allows the service technician to select items to Also, if the temperature in For example, to Press the keypad buttons again and the display will. Priority will Setting for the entire tray would take precedence. Conversely, if the tray was set using option 2 first Guard function. When enabled, the customer will Both states will Allows the service technician to vary the time COOL DOWN feature is started, the time duration of The display will read Allows enabling or disabling the SpacetoSales The display will There are now two choices. Sales vend mode unchanged and return to Configures the SpacetoSales according to user The display will Note This setting overrides any A9

sequentially. After the first item is programmed, the. Press the item In all of the above options, after a selection is The display will For example, If a Vend failseither due to a vend error or no Sales rotation and the VMC will attempt to vend from SpacetoSales block, the customers credit will be The display will If any recheck reads The display will scroll. Recheck setting unchanged and return to NAMA guidelines for health This function provides the customer with an When a retry limit is The display will scroll This means that a Controls sold out detection by the drop sensor.

When enabled, a signal is sent to the VCU when the The display. This setting controls whether the vender displays a Machines with a DixieNarco Technical Service. Press key 5 and the The controller will If the sensor During the This function is used to indicate the state of the Interrupts hot side Provides power to Provides 24 Volt Controller Board. SloBlo; protects 24. Volt input to. Controller Board Board from Varistor Across incoming AC power to remove large Transformer T1 . Fuse X2 Center. Fuse X3 Left Side. Fuse X4 Right Side VAC, 60 Hz, 1 Phase Start Relay. Model 1620CA. Start Capacitor. Thermal Overload. Condenser Fan. Model 1620CA Tl 9660041158 Motor Morrill Motors Evaporator Fan Motor Morrill Motors Transformer T1 . Fuse X4 Right Side. Interrupts hot side Provides power to Provides 24 Volt Controller Board. SloBlo; protects 24. Controller Board Board from Varistor Across incoming AC power to remove large Compressor. Start Relay Start Capacitor 1 1 VAC 1 89227. Thermal Overload 110 VAC Tl MST16AFN Evaporator Fan VAC, 15 Amp circuit U.S. and Canada or 220 VAC, Code and Local Codes and ordinances. Never lubricate the gasket and always check for Replace if necessary. Refer to the Repair any Clean as needed by Ensure nothing To remove. Open the service door. Open the product door. Pull the bin straight out until clear of the When reinstalling, make sure that product delivery Remove power to the AC Distribution Box and Remove the cover from the Control Board if one is Remove the Battery clip to allow the Boards Replace the EPROM. The EPROMs legs bend Replace the Battery clip and cover if used. Apply power to the AC distribution box. Reset. With No Credit Issued Activated Will Not Payback Coins Incorrectly 4 Tube Mech Recommendation Check Mech Tubes. Takes Bill in Then Rejects it. Check Validator or Replace. Stacks Bill While in Escrow Mode. Max Price Not Yet Reached. Bill Error Listed in Test Mode. Communication Error with Bill. Validator.

Bill Validator Reported Error. Takes Bill, Gives No Credit. Board, Harness, Validator. Check or Replace Validator. Harness, Replace Board Out of Order or other error codes RAM Error. Refer to Programming Section on Temp out of Service. No Vendable Selections Should your Disconnected. Apply power. Blown Fuse. Checl. Especially if they have been plugged in and operating instead of sitting unplugged someplace. Storage is not a friend to soda machines. If you do not see what you need, please give us an Email. This control. It fits the DLAA7706 Chute that. They are down on t. This control. These allow you to re. This one has the Plastic coin hoppe. Please help improve it or discuss these issues on the talk page. Learn how and when to remove these template messages Please help by spinning off or relocating any relevant information, and removing excessive detail that may be against Wikipedias inclusion policy. January 2016 Learn how and when to remove this template message Please help improve this article by adding citations to reliable sources. Unsourced material may be challenged and removed.Please help to improve this article by introducing more precise citations. February 2008 Learn how and when to remove this template message Website dixienarco.com. This specific model is exclusive to CocaCola bottlers. The former DixieNarco glass front products are still produced today under the CMS brand.Trump also asserted that the machines had often broken down.The design was updated in 2008 as the Bevmax 3, where the delivery cup height was raised and speeds were increased. In 2009, a further updated version known as the Bevmax 4 was introduced. The Bevmax 4 features even faster vend speeds and is more energyefficient, optionally using LED lighting rather than fluorescent and meeting Tier 2 later updated to Tier 3 Energy Star standards. The Bevmax 4 is available unbranded or through select CocaCola, Pepsi, and Dr PepperSnapple bottlers.

Named for extended cabinet, because it was enlarged fit 20oz.No longer available as of 2009; replaced by the Bevmax 4. AddisonWesley. p. 819. ISBN 0201532859. Retrieved 15 January 2019. By using this site, you agree to the Terms of Use and Privacy Policy. Mounting Option Wall Mounted Automation Grade Manual Get Latest Price from the seller We are a leading manufacturer and wholesaler of Electronic Sanitary Napkin Vending Machine, Electrical Sanitary Napkin Vending Machine, Manual Sanitary Napkin Vending Machine, Easyburn Sanitary Napkin Destroyer Machines, Sanitary Napkin Burning Machine. We are also offering Maintenance Services of our offered machines. Our products are in huge demand in market due to their best prices and superior quality. Our product ranges are hygienically safe and recommended for Hygiene purpose. Our client centric philosophy, sheer dealings, safe shipment, committed time frame delivery and ethical approach towards client makes us completely different from common marketers. We offer our clients with the facility of customization, which imparts them with a feeling of atonement. Apart from the virtual showcase of our products, we welcome our clients to our actual quality so that they can keenly examine the quality of our products. Get Best Deal I agree to the terms and privacy policy All rights reserved.

<http://fscl.ru/content/boss-gt-10b-multi-effects-pedal-manual>