

Dvf-L700 Manual



File Name: Dvf-L700 Manual.pdf

Size: 4896 KB

Type: PDF, ePub, eBook

Category: Book

Uploaded: 2 May 2019, 16:41 PM

Rating: 4.6/5 from 841 votes.

Status: AVAILABLE

Last checked: 2 Minutes ago!

In order to read or download Dvf-L700 Manual ebook, you need to create a FREE account.

[Download Now!](#)

eBook includes PDF, ePub and Kindle version

[Register a free 1 month Trial Account.](#)

[Download as many books as you like \(Personal use\)](#)

[Cancel the membership at any time if not satisfied.](#)

[Join Over 80000 Happy Readers](#)

Book Descriptions:

We have made it easy for you to find a PDF Ebooks without any digging. And by having access to our ebooks online or by storing it on your computer, you have convenient answers with Dvf-L700 Manual . To get started finding Dvf-L700 Manual , you are right to find our website which has a comprehensive collection of manuals listed.

Our library is the biggest of these that have literally hundreds of thousands of different products represented.



Book Descriptions:

Dvf-L700 Manual

It is also quite common that customers throw out User manuals are also Try Google Search! I don't see signal. need a manual PowerAll Slim Plus 9000mAh Portable Battery and PBJS9000SPPLUS Posted by james 20200922 093557 for powerall 9000mAh silver. BLADE X8 LIGHTSOUT Wildgame Innovations Blade X6 Lights Out Trail Camera T6B20 Posted by SCOTT 20200922 043343 LOOKING FOR THIS MANUAL. Operation Simmons LRF600 4x20 Rangefinder 801408C Posted by Terry wheeler 20200922 010205 I depress button unit on depress again for range no range appears just dashes. Create one here. Creators are allowed to post content they produce to the platform, so long as they comply with our policies. United Kingdom. Company number 10637289. Personalizaci a cilenou reklamu si muzete vypnout v nastaveni prohlizece. Doporucene prislusenstvo You get superior, supersampled pictures with noticeably higher contrast, rich colour reproduction and greater clarity. The camera offers robust builtin recording modes, all with vibrant 422 colour. The chassis is only slightly wider than a typical PL mount prime lens, perfect for 3D rigs. An optional shoulder rig provides for handheld and shouldermounted shooting. You get superior, supersampled pictures with noticeably higher contrast, rich colour reproduction and greater clarity. The camera offers robust builtin recording modes, all with vibrant 422 colour. You get superb dynamic range, the widest colour gamut, and pristine image quality, whether you shoot in HD, 2K or 4K I kdyz se snazime o maximalni presnost informaci, bohuzel nemuzeme zarucit jeho 100% spravnost. Poradime vam, podle ceho vybirat nejlepsi digitalni kamery. Shop with confidence. Skip Specifications. Power output 120 watts per channel into 8 stereo. Surround output 75W front, 75W center, 25W rear. Frequency response 20Hz to i push the power button but immediatly the LED turns off. <http://goforthegreengolfpools.com/userfiles/dell-laptop-pp04x-manual.xml>

- **dvf-l700 manual, dvf-l700 manual.**

Manual and User Guide for many equipments like mobile phones, photo cameras, motherboard, monitors, software, tv, dvd, and others. Any one any ideas on why I cant switch it on. Seems like it has gone on lock out. Thanks If so how Please help out. Regards Tommy Did you see this. I have connected it to Philips TV, but there is no signal. I cannot even enter setup on. It looks like the magnet wont release on the dr awer. Can anyone tip me what to do. I solved this by holding the power button down for 510 seconds.. If the error message continues to appear, contact a TEAC Repair Center other than that no solution we have so Where san I obtain same. Register and download the manual for free at retrevo.com. Learn more opens in a new window or tab This amount is subject to change until you make payment. For additional information, see the Global Shipping Programme terms and conditions opens in a new window or tab This amount is subject to change until you make payment. If you reside in an EU member state besides UK, import VAT on this purchase is not recoverable. For additional information, see the Global Shipping Programme terms and conditions opens in a new window or tab Delivery times may vary, especially during peak periods and will depend on when your payment clears opens in a new window or tab. Learn More opens in a new window or tab Learn More opens in a new window or tab Learn More opens in a new window or tab Learn More opens in a new window or tab Learn More opens in a new window or tab Contact the seller opens in a new window or tab and request a postage method to your location. Please enter a valid postcode. Please enter a number less than or equal to 6. Sellers may be required to accept returns for items that are not as described. Learn more about your rights as a buyer. opens in a new window or tab You're covered by the eBay Money Back Guarantee if you receive an item that is not as described in the listing. All Rights

User Agreement, Privacy, Cookies and AdChoice Norton Secured powered by Verisign. More than 480 lines DVD More than 55 dB DVD More than 80 dB Less than 0.01 % There is no Service manuals usually include printed circuit boards, block diagrams, exploded views, assembly instructions and parts catalog. Its invaluable source of information for everyone looking to repair their unit. You should look for Owners Manual. After placing order well send You download instructions on Your email address. Discover everything Scribd has to offer, including books and audiobooks from major publishers. Start Free Trial Cancel anytime. Report this Document Download Now Save Save DVFL700 For Later 0 ratings 0% found this document useful 0 votes 5 views 2 pages DVFL700 Uploaded by Todor Description manual Full description Save Save DVFL700 For Later 0% 0% found this document useful, Mark this document as useful 0% 0% found this document not useful, Mark this document as not useful Embed Share Print Download Now Jump to Page You are on page 1 of 2 Search inside document Browse Books Site Directory Site Language English Change Language English Change Language. The MJL700 squeezes slowly, gently extracting all of the sweet, delicious taste from the ingredients. Pulp is finely strained out for a silky smoothness. You can read more about Shipping at Please close this window and retry the purchase. Ingredients are instantly crushed and then forced downwardThe result is powerful crushing andThe stainless steel screw bottom provides superior durabilityLess pulp in the juice means no unpleasant tasteEven children can safely use the juicer without worry about contacting the moving screw. The Juicing Bowl is made of shatterresistant. TRITANTM from EASTMAN, a beautiful, highclarityAn ideal blend of form and function. If you are thinking about how to survive the heat, don't worry. This unique Mandarin Orange Almond Cake is rich in flavour and will delight everyone you serve it to!

Find the dealer store closest to you by either geolocation or by entering your postcode. You could enjoy FREE delivery for each product purchases, applicable for Malaysia only. Browse our latest selection of Panasonic products range Air Conditioner, Fridge, Washer, TV, Fan, Kitchen Appliances and etc. Discover our attractive offers, purchasewithpurchase deals and premium gifts for our full range of products, including Air Conditioners, Fridges, Washers, Kitchen Appliances, VIERA TVs, LUMIX Cameras and etc. Sony 4K sensor for gorgeous, supersampled HD, 2K and 4K. The PMWF55 CineAlta camera shoots spectacular images with its 8.9 megapixels effective Sony 4K image sensor. You get superb dynamic range, the widest colour gamut, and pristine image quality, whether you shoot in HD, 2K. QFHD or 4K. There is also high speed shooting up to 240 fps. RAW 2K and 60 fps in RAW 4K recording onto the AXSR5. Recording directly in Apple ProRes codec and. Lightweight modular design to maximise versatility in 2D and 3DAs well as the choice of formats and internal and externalOLED viewfinder, PLmount, FZmount and still lenses, including secondgeneration Sony PLmount lenses. The chassis is only slightly wider than aAn optional shoulder rig CBK55BK provides bestVersion 5.0 firmware update. Upgraded functions include DNR Noise. Speed VF setting remains while switching HFR On to Off; and simultaneous recording on SStP 422 SQ atIt is also possible to assign EI value to the Gain Switch in. Wireless AudioSuper 35mm equivalent 4K singlechip CMOS sensor with Frame Image Scan technology. The PMWF55s Sony 4K image sensor captures a true 4K 4096 x 2160 DCIstandard cinema image. Its 4K. CMOS sensor features 11.6 megapixels total and 8.9 megapixels effective. Capture RAW at your choice of resolutions the cameras native 4K or beautiful, derived 2K. RAW recordingSonys 16bit recordingSony RAW retains 16 times as many Red.

Green and Blue gradations as 12bit RAW and 64 times as many tones per channel as 10bit recording. SonyOnce on a PC, the RAW files can be screenedAXSM memory provides a super fast, affordable format forThis is ideal for editing while the hiresolutionHigh speed shooting up to 60 fps 4K and 180 fps 2K internally and 240 fps 2K RAW with optional AXSR5The F55 features highdata rate onboard XAVC HD recordings up to 60 fps, plus a free planned upgrade to. It also offers 240 fps 2K RAW with theThe F55 records internally onto SxS memory. Highspeed shooting

and the highest quality recording options Simultaneous RAW and onboard camera SxS recording For seamless conforming in post, you get matching time code, start Real world workflows with Avid DNxHD codec and Apple ProRes codec recording options. Sony understands a fundamental truth working cameras require practical workflows. That's why the F55 is Recording directly in Apple. ProRes codec and Avid DNxHD codec are also available as hardware options. The DNxHD or ProRes files Vast exposure latitude to 14 fstops. The ability to render tones from deepest shadows to brightest highlights is a crucial test of any digital Sony believes that your camera should not limit your colour palette. That is why the F55 incorporates the You get a colour gamut that's not only wider than other digital cameras, it is even Choice of viewfinders includes amazing OLED technology And the eyepiece flips up for direct monitoring. The DV FL700. Optional shoulder rig. The optional Sony shoulder rig provides comfortable handheld operation, hour after hour. The rig is sturdy, Small lightweight design for added versatility in 3D. The small size of the F55 is particularly welcome in stereoscopic 3D shooting. The chassis is only slightly wider Incredible flexibility with the choice of PL mount, FZ mount and still lenses. The F55 is designed to accommodate PL mount, FZ mount and still lenses. With the PL mount adaptor, you.

There's also Sony's A new generation of Sony PL mount lenses. The F55 works with Sony's second generation, cost effective PL mount prime lenses. Thanks to refined glass, A 9 blade iris The series includes focal lengths of 20, 25, 35, 50, 85 All are the same size except for the 135 mm. Intuitive onetouch interface and customisable user menu Instead of diving through menus, you get direct, onetouch Menu control on sub display also allows you to set up without using the attached Realtime 4K output and other vital connections. The camera offers powerful connections, including realtime 4K output to a compatible monitor. It is made The XLR inputs accept balanced analogue signals, provide Longlife Olivine battery and quick charger. The result is a substantial increase in chargedischarge cycles, compared to previous Sony batteries. The Olivine battery works with Sony's BCL90 quick BCL70 and L160 chargers. Revolutionary electronic Frame Image Scan. The traditional CMOS image sensor uses a rolling shutter that can result in images with unwanted distortions That can be annoying, especially when shooting visual effects or 3D. Anything but typical, the F55 electronic Frame Image Scan. Rolling shutter distortions aren't minimised, they General. DC 12 V 11 V to 17 V. Approx. 25 W while recording XAVC 4K 60p, EVF Off, LCD monitor Off, 4K SDI On Approx. 150 min with BPFL75. Approx. 210 min with BPGL95 AHD SMPTE RP2027 Class 100 compliant. MPEG2 HD MPEG2 Long GOP. XAVC 4K 4096 x 2160. XAVC 2K 2048 x 1080. XAVC HD 1920 x 1080. MPEG4 SStP 1920 x 1080. MPEG2 HD 1920 x 1080. MPEG2 HD 1280 x 720. Camera Section. Super 35mm equivalent Singlechip CMOS PL mount with supplied lens mount adapter. FZ mount without supplied lens mount adapter Preset 3200K, 4300K, 5500K, Memory Standard x6 XLR type 4 pin male x1, 11 V to 17 V DC Digital viewfinder interface x1. BNC x1, HDY or HD Sync trilevel V1.0. BNC x1A Type x1. USB host, type A x1. USB device, Mini B x1. Stereo mini jack x1. Monaural. Media. SD card slot x1.

Supplied Accessories. Lens mount adapter 1. Battery adapter 1. Audio input connector 1. Screws for the audio input connector 4. Tape measure hook 1. Before Using this Unit 1. Operating Instructions CDROM 1. Notes AXS Memory A Series card, 1. TB capacity, 2.4 Gbps AXS Memory A Series card, 1. TB capacity, 4.8 Gbps Option Boards, Modules and Plugins PMWF55 and PMWF5. CineAlta cameras. Batteries and Power Supplies PMWF5 CineAlta cameras PMWF5 software upgrade QFHD recording and Camera Adaptors. SxS Memory Card AXS Memory and SxS. Memory Thunderbolt card AXS media. Tripods and Supports Viewfinders Recorder for F55 and F5 LCD 3.5 inch colour HD Lenses and Lens Adaptors All rights reserved. Reproduction in whole or in part without written permission is prohibited. Features and specifications are subject to change without notice. The values for mass and dimension are approximate. All trademarks are the property of their respective owners. Please check your inbox, and if you can't find it, check your spam folder to make sure it didn't end up there.

Please also check your spam folder. TP 000 119 Rev 1.01 You must return the disk or manual to Verity Systems or an authorized Verity Systems dealer within the warranty period accompanied by proof of purchase. Nor may you rely on such oral or written communication. Some states do not allow the exclusion or limitation of implied warranties or liability for incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights that vary from state to state. If there are missing or damaged parts contact Verity Systems or an authorized distributor immediately. Remove the tape holding down the printer lid. Open the lid and remove the piece of foam holding the CD Tray in place. This packaging was designed specifically for shipping your OptiPrinter PRO. Other packaging may not be suitable.

The lights give you visual clues about the status of the printer. When the action is completed, press the Resume Button to continue printing. If a multiple print command is sent from a PC, the first CD is printed as normal. Then when the CD tray is ejected, the resume light will flash. Place a new CD into the tray and press the Resume button. The CD tray will retract and the CD will be printed and so on for the number of copies requested. It may take a few seconds for the printer to turn on after you press the Power button. The green light flashes when the printer is processing. Using a power strip, surge protector, or a wallmounted switch to turn the printer on and off may cause printer failure. Place a CD onto the tray ensuring that the disc sits against the two pins at the front of the tray as shown below in Fig. 2 The adaptors come in two parts. Close the top cover. If connected, remove the USB and power cables from the printer. There may be variations in the following instructions depending on operating system 2000 or XP and configuration. When prompted, click Install to begin installation. In Windows XP, select Continue Anyway. Switch on the printer. In Windows XP, select Continue Anyway. In Windows XP select No, not at this time and click Next. In Windows XP, select Continue Anyway. For a better experience, please enable JavaScript in your browser before proceeding. It may not display this or other websites correctly. You should upgrade or use an alternative browser. Thanks, Paul Join the AVForums team live on Wednesdays at 7pm UK time. Merci de cliquer sur le bouton cidessous pour donner votre accord. Vous pouvez changer d'avis et modifier vos choix a tout moment. Taille du document 2 Mo 80 pages.

Confidentialite fichier public The handle, The camcorder To measure the To measure the If the four Do not place the lens directly Attach the cover supplied When turning the Stop turning the screw Otherwise, the Direct sunlight can Be sure that its Switching is not executed even The button is enabled while the Press the MENU dial to Replace the cards The stored file can be Press the MENU dial to If the four Be sure that its Press the MENU dial to Balance," "R Gain," or "B The playback picture can be seen When recording, the first You can change the You cannot operate the To start playback without In the CAMERA An uncompleted The current setting Perform the When 8 steps are already Nos partenaires et nous memes utilisons differentes technologies, telles que les cookies, pour personnaliser les contenus et publicites, et analyser le trafic de notre site. You can also download it onto your computer Now kids everywhere can fall in Zuppy Love with Sport, the athletic Zuppy. He loves Contents. 1 Zoomer Zuppy Love; 1 Interactive Toy; 1 Instruction booklet View and Download Spin Master Zoomers training manual online. Featuring breakthrough laser technology, the PowerLite 700U includes a laser light source that lasts up to 20,000 hours 1. Approximate time until brightness decreases 50% from first usage. Time varies depending on usage conditions and environment. Replacement of parts other than the light source may be required in a shorter period. The projector comes with a 3year limited warranty. 2 Color brightness color light output in brightest mode, measured by a thirdparty lab in accordance with IDMS 15.4. Color brightness will vary depending on usage conditions. 3 Color brightness color light output and white brightness white light output will vary depending on usage conditions. Please try again later. You may withdraw your consent or view our privacy policy at any time. To contact Epson America, you may write to 3131 Katella Ave, Los Alamitos, CA 90720 or call 18004637766.

For places in Iran, see Kelisa, Iran. Please help improve this article by adding citations to reliable sources. Unsourced material may be challenged and removed. It was launched in 2001 as the successor to the Perodua Kancil. The Kelisa was sold alongside the older Kancil, and both were eventually replaced by the Perodua Viva in 2007. A limited edition Kelisa, based on the original variant, prominently sports two toned colored paintwork and minor interior modifications. It was available with both manual GXS and automatic EZS transmissions. It was available with both manual GXQ and automatic EZQ transmissions. However, these other names were mainly only used in marketing price lists, brochures, stickers on the boot and more as the vehicles actual registration paper would contain the actual model name. CS1 maint: BOT originalurl status unknown link CS1 maint: BOT originalurl status unknown link CS1 maint: BOT originalurl status unknown link CS1 maint: BOT originalurl status unknown link CS1 maint: BOT originalurl status unknown link CS1 maint: BOT originalurl status unknown link CS1 maint: BOT originalurl status unknown link CS1 maint: BOT originalurl status unknown link CS1 maint: BOT originalurl status unknown link CS1 maint: BOT originalurl status unknown link Retrieved 1 March 2018. By using this site, you agree to the Terms of Use and Privacy Policy. And by having access to our ebooks online or by storing it on your computer, you have convenient answers with Samsung Scl700 Camcorder Manual. To get started finding Samsung Scl700 Camcorder Manual, you are right to find our website which has a comprehensive collection of manuals listed. Our library is the biggest of these that have literally hundreds of thousands of different products represented. I get my most wanted eBook Many thanks If there is a survey it only takes 5 minutes, try any survey which works for you.

Playback mode isn't supported in this firmware release. User can then select "execute" or "cancel" directly. However it takes about 13 seconds to display all of the information which is set to "ON" on the "Output Display" page under "Video" menu. Any key operations including REC button in 13 seconds are disregarded. In other words, an MPEG2 HD422 clip with IN and OUT points edited by Content Browser. However peak hold function displays maximum level correctly. Since current available viewfinders i.e. DVFL350, L700 and EL100, have their own Focus Magnifier button, Focus Magnify function cannot be assigned. Then the card cannot be accepted by the camera. Feel free to contribute. System MANUAL DE INSTRUCCIONES E Espanol. XRDV700 MODE DEMPLOI F FrancaisPage 3 Overloading — Do not allow anything to rest on the power LightningPage 4 OWNERS RECORD System and accessoriesPlacement Allow 15 cm 6 in. clearance. Page 6 ConnectionPage 8 PARTS AND CONTROLS PARTS AND CONTROLSPage 10 Remote controlChanges the menu item selection. Page 11 Display windowPage 13 Changing the display color Select color mode Setting the clock. The display color can be selected from among the preset. Page 14 PREPARATORY INFORMATION PLAYING DISCS—PREPARATORY INFORMATIONSoftware dependent features of DVDs Types of VCDsPage 18 OTHER PLAYBACK MODES PLAYING DISCS—OTHER PLAYBACK MODESProgrammed playback CDs and VCDs Press s again during stop. Locate a point in the title by specifying the time from its Display. Page 22 1When the power cord or plug is damaged or frayed. Page 25 RADIO RADIO. Adjusting delay time. Sounds from the surround speakers and the center speaker arePage 26 Tuning in to preset stations AdjustmentsKeep antennas. Page 27 SOUND SOUNDPage 28 covered by the operating instructions as improper TIMER TIMERThe timeron time, the source and the timeractivated duration.

Page 30 adjustment of other controls may result in damage and will EXTERNAL EQUIPMENT EXTERNAL EQUIPMENTPage 32 To confirm your setting Menu LanguagePage 33 3 Select the desired language and press ENTER. "Others" language code screen appears to select anyPage 34 WIDE TV 4 Press ENTER. Page 35 LANGUAGE CODES Use these numbers to specify the language in the "Disc Languages" setting page 32. Page 36 COUNTRY CODES Use these numbers to specify the country in the "Ratings" setting page 34. Page 37 Code Country Code Country Code Country Code CountryPage 39 SUB WOOFER TSLW700 FIVE SURROUND SPEAKERS SYSTEM SXL700.

Specifications Input FROM CXLDV700U DIN 8pin Front, surround and center speakers. Page 40
NOTE. This equipment has been tested and found to comply with the. The PMW F5's 4K image sensor allows you to record high quality HD pictures. The camcorder adopts the same native FZ mount used by the PMWF3. The camcorder is also compatible with SStP SR SQ 444, SRSQ 422, and SRLite 422 that are adopted for HDCAMSR, or MPEG2 HD 422 that is adopted for XDCAM. Your workflow can be used. High frame rate HFR recording with up to 240 FPS Using the camcorder with the AXSR 5 allows you to perform 2K RAW recording with up to 240 FPS. The camcorder has two scan modes for high frame rate. In the first mode, you can shoot with the full angle of the CMOS image sensor equivalent to the Super 35 mm size, and use the lens with the focal length set for normal shooting of high frame rate recording. In the second mode, you can shoot with the center area of the CMOS image sensor equivalent to the Super 35 mm size cut to Super 16 mm size.
Modular structure The camcorder incorporates a modular design that allows you to configure the camcorder according to shooting circumstances, whether for cinema production, drama, commercials, 3D shooting, documentary filming, interviews, etc.

Wide latitude, low noise The camcorder has a 14 stop latitude that can reproduce images captured by the CMOS sensor with smooth gradation of black to white. Exmor Super35 CMOS technology provides low noise levels, even with 4K resolution and 14stop latitude maintained. A wide variety of recording functions The camcorder has the Interval Rec function that allows you to record frames specified at regular intervals and the Cache Rec function that allows you to begin recording a specified number of seconds in advance of the time that can be used for variety of situations. Single chip design provides stable, highspeed 4K 59.94 P baseband video processing, low power consumption, and compact design. Gamma curves corresponding to various situations The camcorder has a variety of gamma curves corresponding to various situations. SLog2 and SLog3 are equipped to cover wide latitude of the camcorder. The camcorder also has user gamma and hyper gamma. You can select 109 % or 100% for the maximum value of video output White Limit. You can select the video output value with 18% gray card from two values. The camcorder has 5 types of gamma curve and 4 types of Look Profile for Monitor LUT pre set. You can also use any user LUT file that is created by RAW Viewer. Intuitive user interface This camcorder has the color LCD panel on the inside panel, and direct access menu that assigns the commonly used settings to 6 buttons. Displaying the setting information large, makes visibility better. A LOCK switch allows you to prevent changing settings by accident. By using the supplied IFUWL M3 USB wireless LAN module, you can operate the camcorder from a Wi-Fi compatible device such as a tablet, with the wireless transmission. Assignable buttons The inside panel has three assignable buttons, while the outside panel has one assignable button.

You can operate the camcorder easily by assigning commonly used functions to these buttons. The following illustrations are with the battery adaptor page 16 removed. To measure the precise distance between the camcorder and the subject, use this mark or tape measure hook as a reference. Select the ND filter by turning the ND FILTER select switch while pulling it. Set to the OFF position 1 to turn the power off. Turn the MENU dial page 11 to switch the screens in sequence. Camera status screen Displays the electronic shutter settings or the status of the lens. Audio status screen Displays the input settings for each channel, audio level meter, and wind filter setting. System status screen Displays the video signal settings. Video output status screen Displays the video output settings of SDI 1 to SDI 4, HDMI, and test video output. Assignable button status screen Displays the function that is assigned to each ASSIGN button. Battery status screen Displays information of the battery or DC IN power. You can attach the end of a tape measure to the hook, and measure the distance from the subject. 9. VF viewfinder output connector page 26 10. ASSIGN 4 assignable 4 button page 43 Volt a g e Volt a g e V Manufacture Date Manufacture date of the battery Power Source Power source Supplied Voltage Supplied voltage Protect information Remaining Remaining space and available recording time Life Estimate d

service life 1 2 3 5 6 8 9 4 7 10 Audio connector panel page 15 Left side connector panel page 16
Air outlet Air inlet FILE3 page 54 1. to 6. Lens Recall 1 to 6 Loads the Lens file 1 to 6 from the
internal memory. Tip When using the 1.3 or 2 anamorphic lens, set "Aspect" in "VF Setting" page 80
of the VF menu to "Anamo 1.3" or "Anamo 2" to display the normal image without distortion on the
viewfinder screen. SD card indication 15. Time data indication page 43 16.

Focus assist indication page 82 Displays the area that detects the focus status "Focus Area Marker"
and level bar that indicates focus status in the area "Focus Assist Indicator". 17. Clip name
indication page 41 18. Audio level meter 19. The indications are as follows. In the normal situation
The number of segments indicates the strength of the signal level. Muting The number of
transflective segments indicates the strength of the signal level. When "Shooting Mode" page 90
is set to "Cine EI," gamma for a picture that is recorded on an SxS memory card or the Monitor
LUT setting appears. 26. Simultaneous recording status indication page 45 MProxy Displayed
when the function of simultaneous recording on one memory card is effective. 27. Recording
format codec indication page 28 Displays the format that is recorded on an SxS memory card.
28. System frequency and scan method indication page 27 WP Preset mode WM Memory mode Reco
rding format picture size indication page 28 Displays the picture size that is recorded on an SxS
memory card. Displays the imager scan mode 2 KF 2K Full, 2KC 2K Center on the left side of the
picture size. Displays imager scan mode only when recording only RAW format. For safety, use o
nly the Sony battery packs and AC adaptors listed below Lithium ion Battery Pack BPFL7 5 BPL
80S AC Adaptor ACDN2B ACDN10 Attaching a battery pack 1 Attach the battery adaptor supp
lied to the camcorder. Press the release button 1 of the battery adaptor to pop up the ejectio
n lever, then raise the ejectio n lever 2. Insert the projection of the battery adaptor in to the slot
on the rear of the camcorder 1, then lower the ejectio n lever 2. Insert the battery pack into the
battery pack attaching part of the battery adaptor, then slide the battery pack down to lock it in
place.