



File Name: Dvg-1402S Manual.pdf

Size: 2213 KB

Type: PDF, ePub, eBook

Category: Book

Uploaded: 24 May 2019, 12:47 PM

Rating: 4.6/5 from 561 votes.

Status: AVAILABLE

Last checked: 13 Minutes ago!

In order to read or download Dvg-1402S Manual ebook, you need to create a FREE account.

[**Download Now!**](#)

eBook includes PDF, ePub and Kindle version

[❑ Register a free 1 month Trial Account.](#)

[❑ Download as many books as you like \(Personal use\)](#)

[❑ Cancel the membership at any time if not satisfied.](#)

[❑ Join Over 80000 Happy Readers](#)

Book Descriptions:

We have made it easy for you to find a PDF Ebooks without any digging. And by having access to our ebooks online or by storing it on your computer, you have convenient answers with Dvg-1402S Manual . To get started finding Dvg-1402S Manual , you are right to find our website which has a comprehensive collection of manuals listed.

Our library is the biggest of these that have literally hundreds of thousands of different products represented.



Book Descriptions:

Dvg-1402S Manual

It can reduce long distance phone charges and deliver tollquality voice communication over the IP network. This gateway provides two loop start Foreign Exchange Subscriber FXS ports and four LAN ports. This option is commonly used for Cable modem services. Host Name The Host Name is optional but may be required by some ISPs. The default host name is the device name of the Router and may be changed. MAC Address The default MAC Address is set to the WAN's physical interface MAC address on the BroYou can use the "Clone MAC Address" button to copy the MAC address of the Ethernet Card installed by your ISP and replace the WAN MAC address with the MAC address of the router. It is not recommended that you change the default MAC address unless required by your ISP. Enter a DNS Address if you wish not to use the address provided by your ISP. The upstream bandwidth can be set for the data traffic. The Upstream Bandwidth bandwidthEach IP address entered in the fields must be in the appropriate IP form, which are four octets separated by a dot x.x.x.x. The Router will not accept the IP address if it is not in this format. IP Address Input the public IP Address provided by your ISP. Subnet Mask Input your Subnet mask. All devices in the network must have the same subnet masThis option is typically used for DSL services. PPPoE Choose this option if your ISP uses PPPoE. Most DSL users will select this option. Password Enter The PPPoE user name provided to you by your ISP. Retype Password Retype the password entered in the previous field. Service Name EntThe upstream bandwidth can be set to suit the type of packets Upstream that the connection will be sending. These are the IP settings of the LAN interface for the DVG1402S and may be referred to as Private settings. You may change the LAN IP address if needed. The LAN IP address is private to your internal network and cannot be seen on the Internet. IP Address The IP address of the LAN interface. The default IP address is 192.168.15.1. <http://adrijaadrika.com/userfiles/dell-laptop-inspiron-1200-manual.xml>

- **dvg-1402s manual.**

Subnet Mask The subnet mask of the LAN interface. The default subnetThe phone will then use the domain name in Domain Name field as part of SIP URL but send and receive SIP messages through the SIP proxy server defined in the Service Domain field. IP Address Enter the IP address of the SIP Server in this field. Domain Name Enter the domain name corresponding to the IP address entered above in this field. Port Enter the SIP server's listening port for the SIP in this field. Leave this field set to the default if your VProvisioning Function Use this dropdown menu to Enable or Disable the Provisioning Function on the router. Server URL Enter the URL of the Provisioning Server in this field. Proxy Address Enter. Youll find such information in the Manual of your DLink DVG1402S router. But if you do not have the manual for your router or you do not want to read the whole manual to find the default login information then you can use the quick guide below. To get to the router login page its necessary that you are connected to the router. The default password is admin. Sometimes the username and password doesnt work that we mentioned in the top of this guide. Did you try the following IPs In the list below we listed all known router IPs for the manufacturer DLink. Maybe this will work for you. This can be done easily by clicking on the reset button at the back or at the bottom of your router. If you hold down this small button for approximately 20 seconds, you may have to use a toothpick, then your modem will get restored to the factory settings. What you need to keep in mind is that when you reset your modem, you will lose your connection online. It is therefore better to take an experts assistance in this regard. Callcentric and our customers have found the DLinks DVG1402S to not be a particularly reliable device; and we cannot recommend it. http://practicmed.ru/files/dell_laptop_e1505_ma.xml

It may be possible depending upon your contract to have the device unlocked by the provider; but if you do not have full access rights including all usernames and passwords to the device you will not be able to use the device with Callcentric. The DVG1402S can be used with Callcentric. We recommend that you read each step through in its entirety before performing the action indicated in the step. If you will be using the DVG1402S as a router connect your broadband connection such as cable modem or DSL modem to the WAN port on the DVG1402S. Connect your computer to the LAN ports on the DVG1402S. For more detailed instructions please refer to the DVG1402S manual. If you will be using the DVG1402S behind your existing broadband router connect the WAN port on the DVG1402S to your router or LAN. NOTE If you plan on setting up the DVG1402S behind your existing router you will need to first plug a computer into the LAN ports on the DVG1402S in order to configure it. The DVG1402S cannot be configured via the web interface from the WAN port. After connecting the network cables, connect your phone to the DVG1402S. Finally plug the supplied power. If you have changed the IP address, or this does not work, you will need to reset your DVG1402S to factory defaults as explained here. Click the button Login to the webbased management module. The defaults are supplied below: User name admin Password admin. NOTE If this username/password combination does not work it is because you have either changed the username and password which can be set back to default by resetting the DVG1402S to factory defaults as explained here; or your DVG1402S has been locked by the provider you purchased it from and you must contact them to obtain the username and password. Click on the link Your extension SIP password is the password you created for the extension you are trying to use.

You may edit the SIP password you wish to use in by logging into your My Callcentric account and clicking on the Extension menu link and then modifying the appropriate extension. Your extension SIP password is the password you created for the extension you are trying to use. You may edit the SIP password you wish to use in by logging into your My Callcentric account and clicking on the Extension menu link and then modifying the appropriate extension. Wait 60 seconds for this process to finish. You can make a test call to 17771234567, or if you are signed up for one of Callcentric's rate plans you. Since this firewall blocks incoming connections you may need open a port through it for certain games and applications. This process of opening a port is frequently called a port forward, since you are forwarding a port from the internet to your home network. That's why we created Network Utilities. Our software does everything that you need to forward a port. This ensures that your ports will remain open even after your device reboots. Your router has a web interface, so you will login to it using your web browser. This can be either Chrome, Firefox, Internet Explorer, or Edge. It usually does not matter which browser you choose to use. It should look something like this. Your router's IP address can also be referred to as your computer's default gateway. If all goes well you will see the following screen. Here's how you do it. Starting from the first page in your router. In this new menu, click Configure Lan Port. In this new menu, click Nat Configuration. In this new menu, click Virtual Server Configuration. If you are forwarding a range of ports, enter the lowest number of that range into the left global port range Start Port, local port range Start Port box. Then enter the highest number of that range into the right global port range End Port, local port range End Port box. Our Open Port Check tool is the only online port checking tool with Guaranteed Results.

Built-in Firewall Protects Your Network ". Connect up to Two Standard Telephones for Low-Cost Calling ". Compatible with Multiple Call Features Including Call Waiting, Caller ID, and More. All company, product and service names used in this website are for identification purposes only, and do not imply endorsement. By continuing you are giving consent to cookies being used. Download the TFTP program, you will find it on the following link. Unpack both the firmware and the TFTP program to the same folder ex. C:\firmware. Start up the TFTP program by doubleclicking on tftpd32.exe. Type in the following. TFTP Server Address This is the address to your PC that you can see

in the TFTP program onFirmware Update Should be set to Enabled. File Name The filepath to the upgrade ex. See the picture below for an example. Click on the button Apply to commence the upgrade procedure. This will take a couple of minutes. DO NOT power off the unit during the upgrade process! IMPORTANT! An upgrade should never be performed over a wireless connection! Check Your Package ContentsEther CAT5. UTP CableUsing aHardware Overview. Front Panel. PowerGreen light indicates a normal power supply. A fastTelephone Adapter is communicating with the Auto. Provision Server. When a connection is established the 10 or 100 LED willRear PanelA. Insert one end of the Ethernet cable into the WAN port on the back of. LAN port of your router or an available Ethernet port on your PC. B. Insert a telephone cable into the Phone port, and then connect theC. Connect the power adapter to the power input at the back panel ofOn the front of the device, the Power LEDD. Check the LED display on the front of the VoIP Telephone Adapter toAfter the installations are completed, your network should look similar toHardware configuration is complete. If your VoIP service is already activated, youTo access the webbased configuration utility, open a web browser suchOpen your Web browser andClick Login to enter Web Site.

Click Setup Wizard.Click Next. The username of ADMIN and USERClick Next. Enter a NTP server or use theDaylight Saving for your local time ifClick Next.Select your Internet connection typeSelect Manual to manually enter IPDNS is assigned by ISP. Click Next. Register to the SIP Proxy Server byProxy Server. Enter Proxy Server. The Outbound Proxy Support isRegistration by phone line enter. Password supplied by your ITSP. Click on the Register check box toClick Next.Setup is finished. Check theClick Restart. Discover everything Scribd has to offer, including books and audiobooks from major publishers. Start Free Trial Cancel anytime. Report this Document Download Now Save Save Manual Dvg 1402s For Later 0 ratings 0% found this document useful 0 votes 73 views 20 pages Manual Dvg 1402s Uploaded by Wanderson Ribeiro Description Full description Save Save Manual Dvg 1402s For Later 0% 0% found this document useful, Mark this document as useful 0% 0% found this document not useful, Mark this document as not useful Embed Share Print Download Now Jump to Page You are on page 1 of 20 Search inside document Browse Books Site Directory Site Language English Change Language English Change Language. Unlimited local, long distance, and international calls can be made with the included Lingo voice service. Also enjoy additional features such as Caller ID, Voicemail, 3Way Calling, Call Forwarding. Products and names mentioned are the property of their respective owners. Em baixo do equipamento ha um chaveador para que seja efetuada a mudanca de modo de configuracao. Neste caso, Em baixo do equipamento ha um chaveador para que seja efetuada a mudanca de modo de configuracao. Neste caso, Voce mesmo instala e configura, sem a necessidade Internet Explorer 6 ou Netscape Navigator 7 ou superior.

DSL2730B Roteador ADSL Wireless Antes de comecar Certifique-se Segue um exemplo de topologia a que o equipamento atende Segue um exemplo de topologia a que o equipamento atende 1 1 Para configurar o DPR1260 conecte um cabo de rede na porta LAN do DPR1260 ate Clique em Register para efetuar o cadastro de um novo grupo.foto Siemens Roteador VoIP SpeedStream 3610 O IP de seu DLink DVG5121SP por padrao e 192.168.1.1 Figura 1 1. Para acessalo, Dessa forma pode simplificar a infraestrutura Clique na opcao VOIP, depois opcao configuracao conforme as imagens Abra o software de programacao. Clique Utilizaremos como exemplo a camera DCS5300W. 1 Antes de iniciar a configuracao Apos finalizar a configuracao, seu computador obtera o IP e a pagina de configuracao do ATA podera ser acessada. O LED WAN acendera; 3. Conecte a porta LAN a placa de rede do PC. O LED LAN acendera; 4. Conecte os telefones Voce mesmo instala e configura, sem a necessidade Os 2 equipamentos estao interligados pelos roteadores Para realizar a configuracao d, e necessario que o computador Centro de Computacao Cientifica e Software Livre C3SL Siga todos os topicos para que seja feita a configuracao basica para Manual de configuracao em modo PPPoE Roteamento do modem TG581n, avancado. Para realizar a configuracao d, e necessario que o

computador que sera utilizado esteja com as configuracoes Significado de cada LED. Conteudo da embalagem. Instalacao e Configuracoes Para realizar a configuracao d, e necessario que o computador que sera utilizado esteja Configuracao Instalacao do SQL 2005. Primeiro baixo o instalador do SQL nesse link Execute o arquivo Faca o download do aplicativo do seguinte endereco Neste manual iremos apresentar os tipos de configuracoes possiveis.

Para melhor entendimento deste manual e preciso Voce mesmo instala e configura, WPS RESET SIM 3 Ligue a fonte de alimentacao de energia A primeira parte e onde Com este guia voce pode realizar a instalacao To use this website, you must agree to our Privacy Policy, including cookie policy. New DLink VoIP Gateway DVG1120M in original box with accessories. This means that any manual settings for port This would instruct the DLink adapter to route any calls starting with 416 to be D Link Dvg 5112s Manual DVG1102M Dlink DVG1120M Dlink DVG1120Mv2 Dlink DVG1402S Dlink. Gateway DLink DVG2004S Quick User Manual. Voip Tony stretton sample exam 523, Swimming best form of exercise, Management project report, Sample strategic management case analysis, Carfax car report. Reload to refresh your session. Reload to refresh your session. Conexoes do VoIP Router Conecte o VoIP Router ao computador utilizando o cabo Ethernet que compoe o Kit VoIP e a rede eletrica utilizando a fonte de alimentacao. Conectando os telefones Conecte os aparelhos telefonicos ao VoIP Router. Observacao As luzes Phone "1" e "2" acendem quando os telefones respectivos estao fora do gancho. Configuracao dos Parametros de Usuario e Senha para Acessos de Banda Larga do Tipo PPPoE. Alguns provedores de acesso a Internet de banda larga utilizam o protocolo PPPoE para a autenticacao de seus clientes no momento da conexao. Neste caso, sempre que o cliente quiser navegar pela internet, sera necessario informar o nome de usuario e senha cadastrados com este provedor. Com a instalacao do VOIP ROUTER DVG 1402S voce nao precisara mais fornecer estas informacoes a cada acesso, pois a autenticacao sera feita diretamente entre o seu provedor e o VOIP ROUTER.

Page 1 and 2 Manual para configuracao DLINK D Page 3 and 4 Guia de instalacao DLINK DVG140 Page 5 Visualizando Hardware Painel Trasei Page 9 and 10 Nesta tela, selecione GMT 0300 e Page 11 and 12 Na area de trabalho do seu computa Page 13 and 14 Nesta tela, clique em Restart para Page 15 and 16 Selecione a opcao Dynamic IP Addr Page 17 and 18 Altere os campos Same Phone Number Page 19 and 20 CARACTERISTICAS TECNICAS Portas d Thank you, for helping us keep this platform clean. The editors will have a look at it as soon as possible. I have a dlink router that I want to connect my iPad to.The DHCP server of the DVG1402S will not be updated with the new LAN IP information automatically. It will have to be updated manually. Choose from the full product listIf you want to use the chat log, please. Prohlednete si VoIP brana DLink DVG1402S. Prezrite si VoIP brana DLink DVG1402S. Please email us if youre running the latest version of your browser and you still see this message. The actual Open Box product may differ in packaging and included accessories, but has been tested to ensure basic functionality. It has taken dozens of hours sitting on the phone between Lingo and DLink as each of the two organizations would not discuss the issues between them. When I received it I set it up to ensure all was operational. I then signed up for Lingo service. When on the call I dropped to 70Kbps download and 38kbps upload. When I hung up I never got the bandwidth back until I rebooted the DLink box. Level 3 DLink support reported to me today they have no fix currently and none in sight. I discussed this with the Lingo support group. They said it was DLinks problem. I discussed this with DLink and they said it was Lingos problem. I suggest since both companies agreed on this device to support Lingos VoIP business, then both companies should work together to resolve these problems and not have the customer be the problem manager between the two companies.

I have quite a bit of technical information that Ive gathered but it seems as no one really cares. My original plan was to move from Vonage to Lingo as Lingo has an area code which I need that Vonage does not. I will make this decision within the next week whether to cancel Lingo and return the

DLink to NewEgg or keep Lingo and cancel Vonage. I simply can't afford to have two different phone services at this time. Vonage operationally has been no problem over the past year and a half; I suggest Lingo should be of the same quality but isn't. I had the Lingo provided router assigning DHCP to my network. That router was junk. I replaced it with this router had to create a new Lingo account though and resolved a lot of issues with my Lingo service. Having to start the new Lingo account qualifies me for the mail in rebate. Bonus! Replacing my router with this one actually increased my throughput from 3,000kbps to 4,800kbps. Works great, no complaints here. Avoid Lingo, they outsourced their tech support, and their techs are poorly trained, you will experience consistent problems such as disconnects, echoes, inability to call out, inability to receive calls, etc. The techs answer will always be to move you to a different server. Do yourself a favor, avoid Lingo! Followed directions to set up the Router and Lingo services and could not make a call once it was set up. I kept getting a busy signal if I tried to make a call. Plus I could not call into the phone. I called using my cell phone, of course Lingo's support and after about 45 minutes, they fixed the problem. According to the tech, there was a security key or something that was preventing my router to authenticate on their server. I've had the service for about 2.5 weeks and I can't complain. I have a cable modem with Comcast as the ISP if you would like to know. Can't go wrong with this product, plus after the mail in rebate, it's practically free. Ohhh, NewEgg, once again rocks. Ludicrous speed on processing and shipping!

The casing is extremely durable, not that you would take it offroad or anything. This would be a definite buy if you can't find one cheaper. [Click here for more details.](#) Secure shopping made faster. Check out with PayPal. Any exceptions to the condition of the item outside the manufacturer's information should be provided in the listing, up to and including warranty details. Any accessories MAY OR MAY NOT be included. NewEgg will NOT send you any missing accessories, even if it is required to use all of the item's functions. Open Box items usually do not come with manufacturer or vendor warranty or technical support. However, warranty support may be available if an item was never registered by a previous owner. Please contact the manufacturer to check. Product may include warranty, and accessories found with the original product. Product may or may not be in the original packaging. Returned items with minor packaging defects fall under this category. Product does not come with warranty unless stated otherwise in product description. Product does not come with warranty unless stated otherwise in product description. Product does not come with warranty unless stated otherwise in product description. Functionality issues beyond signs of use should be disclosed in product description. Some manufacturers place restrictions on how details of their products may be communicated. Some manufacturers place restrictions on how details of their products may be communicated. Some manufacturers place restrictions on how details of their products may be communicated. Some manufacturers place restrictions on how details of their products may be communicated. DLink DVG1402S Router Internal IP Address Open link Voila! You are now logged in! Of course, you can build a strong hash password with special character, numbers, greek and latin. But ultimately you will end up writing it on a sticky and putting it on the router which defeats the purpose.

Look for Network Name SSID, this is the wifi name of your DLink DVG1402S Router. Once you enter the name for your network, you have to enable WPA2PSK encryption on your DLink DVG1402S router. That's the strongest encryption standard available for home networks. Keep it 1620 characters and please! don't use the same password that you used for DLink DVG1402S router login. You did good so far, Now consider. Bookmarking this page, It always helps Just forget, We don't even recommend it 6. Security is a continuous process Just keep in mind to change the passwords often or at least once in every 6 months. Time for a bulletin on the fridge, folks. We can remind you though. Enter your email on below. Nope, we're not spammers! submit Or, in most cases, users find a way to forget them. In either case, look up the "How to Reset the DLink DVG1402S Router to Default Settings" section below Forgot Password to DLink DVG1402S Router In case if you have

changed the default username and password of DLink DVG1402S and forgot it, Please see “How to Reset the DLink DVG1402S Router To Default Settings” section below How to Reset the DLink DVG1402S Router To Default Settings Incase if you have changed the default username and password of DLink DVG1402S and forgot it, It’s more like magic, I’d say. Press the reset button with a pin or something that gets through the tiny hole, and hold it for about 15 seconds! till you see all lights flickering Your DLink DVG1402S router shall be reset in no time, and you can start from step 1 in this guide to set it back up We are looking for Sponsors. Modemly helps hundreds of thousands of people every month to setup a safe and secure internet environment. We are looking for sponsors for our site Read more How to boost DLink DVG1402S Wifi and overcome connectivity issues 1.Place the DLink DVG1402S in a perfect spot The perfect spot does it all; be it romance or your router.

To avail the best signal and network connectivity, make sure you keep your DLink DVG1402S router visibly and not facing the wall or behind the curtains 2.Find a Good Wireless Channel Instead of Auto on your DLink DVG1402S router Auto channels might fail you once in a while; believe that you’re smarter than the DLink router. Find a seamless wireless channel instead of what the router finds automatically. This would ensure that your signal does not interfere with that of your neighbors. Open Command prompt In command prompt type netsh wlan show all You will see a list of all wireless networks and the channels being used in your vicinity.This means that if possible, you should consider hardwire using Ethernet cable the devices that tend to consume a lot of bandwidth. Although this can sort of defeat the purpose of having wireless network, but it can actually help your overall network speed of DLink DVG1402S if you can hardwire the bandwidth hogs. 5. Reboot DLink DVG1402S on a schedule Here is something important to note. On schedule, folks, reboot your DLink DVG1402S router. Though routers are built to constantly be running at all times, simple tweak like regular power cycling a fancy way of saying unplugging the power cord and shoving it back up helps with most issues. Rebooting your DLink DVG1402S can fix Internet connection problems, improve slow moving connections and resolve wireless issues altogether. Try unplugging your DLink modem on a quarterly basis to stay proactive Never reset, always reboot modem. The DVGG1402S is designed for VoIP service providers and resellers to bundle their existing VoIP services and create a consistent, reliable, and exible VoIP Netorking Solution. The DVGG1402S is a router with 802.11g wireless that facilitate users to easily network all of their computers and other networking devices together and share internet access. The DVGG1402S also enables end users to use their existing analog telephones with VoIP phone service.

It comes with two 2 FXS ports to allow end users the exibilities to either connect up to two analog phones or an analog phone and a FAX machine for small ofce environment. The DVGG1402S supports the SIP voice protocol, which is the widely deployed by VoIP providers on the market. It also supports the basic telephony features such as call waiting and caller ID. For security, all conguration settings are protected and only VoIP service provider or reseller with authenticated user name and password can access the settings. The DVGG1402S supports multiple audio CODECs to ensure consistent voice quality and to eliminate echoes. The integrated QoS provides three levels of voice packet control to ensure reliable call quality and to prevent dropped calls and voice “cracking”. The DVGG1402S Wireless Broadband VoIP Router provides all of the necessary elements to create a robust voice and data network for home or SOHO environments by combining VoIP with network router. The DVGG1402S combines VoIP and networking solution to simplify the home networking infrastructure. Above all, The DVGG1402S will help customers to control their budget by not having to purchase all of the hardware individually. Telephone calls made over the Internet VoIP maximizes your broadband investment and is a costeffective way to make phone calls. With the DVG1402S, calling over the Internet is simple and works just like a regular telephone. The DVG1402S is compatible with several convenient call features such as caller ID, voicemail, call waiting, and three way calling. The DVG1402S Broadband Phone Service VoIP Router also acts like a router for your network, providing room to connect up to 4 computers to share a Broadband Internet

connection.

With all the essential features in a router and featuring PPPoE support for DSL accounts, router functionality for access to the Internet, and firewall features to keep unwanted intruders out of the network, the DVG1402S is an allaround solution for the home, office, or small business. All DLink products. DLink DVG1402S Router IP Address Open link You can easily reset the DLink DVG1402S router by pressing and holding the reset button with a clip for about 15 seconds. Retry the credentials again and voila, youre in. Give yourself a pat on the back, youve completed the hardest steps without any hassle on your DLink DVG1402S Router.Heres what you do nextSimilarly, for your device to receive incoming traffic you will have to create a new port forwarding rule on your DLink DVG1402S Router. That is going to be our very last step. Stick with me now, youve done great so far, Better yet. Bookmark this page, it always helps.Lets go ahead and perform a few tests to ensure we havent goofed up.Theres lot of port checkers available online.You can now host private game servers or effortlessly access your IP camera from the outside world.We can remind you though. Nope, we're not spammers!Well, there's a reason, Wise men said "The opposite of Networking is Not Working". So, it does take some trial and error to get it working.To find out, log in to your DLink DVG1402S Router and check the IP address on the status page.Follow step 1 in this guide, reboot your device and confirm the IP hasnt changed. Now youre good to go. In few cases, though the static IP is enabled correctly, a reboot may be required for proper IP recycling. Well, Reboot does workYou also would not enter LAN IPs or your own public IP.Some router developers are producing routers with more builtin firewall. While this is definitely a positive, some of these options could restrict incoming connections even if a port forwarding rule is set on DLink DVG1402S Router. Thankfully we programmers are a humble lot.